

Application No.10/014,620
Filed: November 9, 2001
TC Art Unit: 2663
Confirmation No.: 1439

AMENDMENT TO THE CLAIMS

1. (Original) A method of propagating link state information in a routing area of a network including a plurality of routers, comprising:

generating a node state advertisement at a first router of the plurality of routers, the node state advertisement identifying the first router and a link about which the first router desires to receive link state information;

flooding the node state advertisement throughout the routing area so as to ensure that substantially all of the plurality of routers receive the node state advertisement;

at each of the routers receiving the node state advertisement, determining whether the receiving router lies along a path meeting a predetermined criteria between the link and the first router; and

at each of at least one second router determined to lie along such a path, (1) maintaining an association between the link and the first router, the association indicating that link state advertisements concerning the link are to be forwarded along the path toward the first router, and (2) upon a change of the state of the link, forwarding a corresponding link state advertisement to an adjacent one of the routers along the path toward the first router.

2. (Original) A method according to claim 1, wherein the predetermined criteria is that the path be the shortest path between the link and the first router.

3. (Original) A method according to claim 1, wherein maintaining the association between the link and the first router comprises storing a next hop node identifier with a link state entry for the link, the next hop node identifier identifying the adjacent one of the routers.

4. (Original) A method according to claim 1, wherein the change of the state of the link comprises a change in unreserved bandwidth of the link.

5. (Original) A method according to claim 1, wherein the change of the state of the link comprises a change in latency of the link.

Application No.10/014,620
Filed: November 9, 2001
TC Art Unit: 2663
Confirmation No.: 1439

6. (Original) A method according to claim 1, wherein the change of the state of the link comprises failure of the link.

7. (Original) A method of performing protection switching in a network, comprising:

broadcasting a node state advertisement from an ingress node of a primary communications path in the network, the node state advertisement identifying the ingress node and a link included in the primary communications path, the ingress node transmitting ingress data traffic on the primary communications path in the absence of a failure thereon;

flooding the node state advertisement throughout a routing area of the network so as to ensure that substantially all of a plurality of routers in the routing area receives the node state advertisement;

at each of the routers receiving the node state advertisement, determining whether the receiving router lies along a desired signaling path between the ingress node and the link;

at each of the routers determined to lie along the desired signaling path, (1) maintaining an association between the link and the ingress node, the association indicating that link state advertisements concerning the link are to be forwarded along the desired signaling path toward the ingress node, and (2) upon a change of the state of the link, forwarding a corresponding link state advertisement to an adjacent one of the routers along the desired signaling path toward the ingress node;

at a designated router for the identified link, upon a failure of the link, originating a link-state advertisement indicating that the link has failed, and forwarding the link-state advertisement to an adjacent one of the routers along the desired signaling path toward the ingress node; and

at the ingress node, upon receipt of the link-state advertisement indicating that the link has failed, switching the ingress data traffic from the primary communications path to a backup communications path.

Application No. 10/014,620

Filed: November 9, 2001

TC Art Unit: 2663

Confirmation No.: 1439

8. (Original) A method according to claim 7, wherein the desired signaling path is the shortest path between the link and the ingress node.

9. (Original) A method according to claim 7, wherein maintaining the association between the link and the ingress node comprises storing a next hop node identifier with a link state entry for the link, the next hop node identifier identifying the adjacent one of the routers.